

VMU plus, VMU plus 150 (Comp. A)	, VMU plus 280, VMU plus 3	00, VMU plus 345, VMU plus 410
Revision date: 14.10.2022		Page 1 of 11
SECTION 1: Identification of	f the substance/mixture and o	f the company/undertaking
<u>1.1. Product identifier</u> VMU plus, VMU plus 150,	VMU plus 280, VMU plus 300, VML	J plus 345, VMU plus 410 (Comp. A)
UFI:	U930-U9U6-9300-ATXP	
1.2. Relevant identified uses o	f the substance or mixture and us	ses advised against
Use of the substance/mixtu Adhesive mortar for faster Uses advised against no restriction	re ning elements A-component (resin)	
1.3. Details of the supplier of t Company name: Street: Place:	<u>he safety data sheet</u> Sikla GmbH In der Lache 17 D-78056 VS-Schwenningen	
Telephone: e-mail: e-mail (Contact person): Internet:	+49(0)7720 948 0 info@sikla.de info@sikla.de www.sikla.de	Telefax:+49(0)7720 948 337
1.4. Emergency telephone number: SECTION 2: Hazards identif		inchen, German and English 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol Warning

Signal word:

Pictograms:



Hazard statements

H317

May cause an allergic skin reaction.

Precautionary statements

ooddionary olde	
P261	Avoid breathing vapours.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulat	ion)		
2082-81-7	Tetramethylene dimethacrylate			5 - < 20 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1B; H317			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			1 - < 8,5 %
	248-666-3	01-2119490226-37		
	Eye Irrit. 2, Skin Sens. 1; H319			
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			< 1,25 %
	254-075-1		01-2119980937-17	
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 20 %
	dermal: LD50	= > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	1 - < 8,5 %
	dermal: LD50	= > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropan-2-ol	< 1,25 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Page 2 of 11

VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410

(Comp. A)

Revision date: 14.10.2022

May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam Extinguishing powder Water spray jet Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Page 3 of 11

VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 4 of 11

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed.
- Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
2082-81-7	Tetramethylene dimethacrylate			
Worker DNE	L, long-term	inhalation	systemic	14,5 mg/m³
Worker DNE	L, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	4,3 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DI	NEL, long-term	oral	systemic	2,5 mg/kg bw/day
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNE	L, long-term	inhalation	systemic	14,7 mg/m³
Worker DNE	L, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	8,8 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DI	NEL, long-term	oral	systemic	2,5 mg/kg bw/day
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			
Worker DNEI	L, long-term	inhalation	systemic	2 mg/m³
Worker DNEL, long-term		dermal	systemic	0,6 mg/kg bw/day
Consumer DI	NEL, long-term	oral	systemic	0,3 mg/kg bw/day
Consumer DI	NEL, long-term	dermal	systemic	0,3 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	0,4 mg/m ³



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 5 of 11

PNEC values

CAS No	Substance	
Environment	tal compartment	Value
2082-81-7	Tetramethylene dimethacrylate	
Freshwater		0,043 mg/l
Marine wate	r	0,004 mg/l
Freshwater s	sediment	3,12 mg/kg
Marine sedir	nent	0,312 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	2 mg/l
Soil		0,573 mg/kg
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	
Freshwater		0,904 mg/l
Marine water		0,904 mg/l
Freshwater sediment		6,28 mg/kg
Marine sediment		6,28 mg/kg
Micro-organi	sms in sewage treatment plants (STP)	10 mg/l
Soil		0,727 mg/kg
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	
Freshwater		0,017 mg/l
Marine water		0,0017 mg/l
Freshwater sediment		0,0783 mg/kg
Marine sedir	nent	0,0072 mg/kg
Soil		0,005 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves Recommended material: NBR (Nitrile rubber) Breakthrough time: > 480 min Thickness of the glove material: > 0,2 mm DIN-/EN-Norms EN 374



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 6 of 11

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)	
Colour:	light beige	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and		not determined
boiling range:		
Flammability:		not determined
		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		not applicable
Decomposition temperature:		not determined
pH-Value:		not determined
Water solubility:	The study does not need	to be conducted
······································	because the substanc	
	in	soluble in water.
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density (at 20 °C):		1,71 g/cm³
Relative vapour density:		not determined
9.2. Other information		
Information with regard to physical	hazard classes	
Self-ignition temperature		
Solid:		not determined
Gas:		not applicable
Oxidizing properties		
Not oxidising.		
Other safety characteristics		
Evaporation rate:		not determined
Solid content:		not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 7 of 11

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 2499,1 mg/kg; ATE (inhalation vapour) 4900,00 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2082-81-7	Tetramethylene dimeth	acrylate			
	oral	LD50 10066 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rabbit		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
38668-48-3	1,1'-(p-Tolylimino)dipro	pan-2-ol			
	oral	LD50 > 25 - < 200 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 8 of 11

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
2082-81-7	Tetramethylene dimetha	acrylate					
	Acute algae toxicity	ErC50 mg/l	9,79	72 h			
	Crustacea toxicity	NOEC mg/l	5,09	21 d			
27813-02-1	Methacrylic acid, monoe	ester with p	propane-1,2	2-diol	_	_	
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	> 143		Daphnia magna (Big water flea)		
	Algae toxicity	NOEC	mg/l				
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol						
	Acute fish toxicity	LC50	17 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50	245 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	28,8		Daphnia magna (Big water flea)		
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus		OECD 201

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
2082-81-7	Tetramethylene dimethacrylate					
	OECD 310	84 %	28			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	OECD 301C	81%	28			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1

12.4. Mobility in soil

The product has not been tested.



Sikla GmbH

VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:No dangerous good
No dangerous good
No

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. Page 9 of 11



Sikla GmbH

VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 10 of 11

<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 75 Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

VOC content: 6,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labeling and Packaging DMEL: Derived Minimal Effect level **DNEL: Derived No Effect Level** EC50: Effective concentration, 50% ErC50: EC50 in terms of reduction of growth rate IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. A)

Revision date: 14.10.2022

Page 11 of 11

IMDG: International Maritime Code for Dangerous Goods LC50: Lethal concentration, 50% LD50: Lethal dose, 50% NOEC: No Observed Effect Concentration OECD: Oragnisation for Economic Co-operation and Development PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail) VOC: Volatile organic compound Acute Tox. 2: Acute toxicity, Category 2 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Sens. 1: Skin sensitilization, Category 1 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H300	Fatal if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)		
Revision date: 14.10.2022		Page 1 of 11
SECTION 1: Identification of	of the substance/mixture and of t	the company/undertaking
<u>1.1. Product identifier</u> VMU plus, VMU plus 150,	VMU plus 280, VMU plus 300, VMU p	olus 345, VMU plus 410 (Comp. B)
UFI:	WD30-C9HK-K30H-05HR	
1.2. Relevant identified uses o	f the substance or mixture and uses	<u>s advised against</u>
Use of the substance/mixtu compound mortar B-comp		
Uses advised against no restriction		
1.3. Details of the supplier of t	he safety data sheet	
Company name: Street: Place:	Sikla GmbH In der Lache 17 D-78056 VS-Schwenningen	
Telephone: e-mail: e-mail (Contact person): Internet:	+49(0)7720 948 0 info@sikla.de info@sikla.de www.sikla.de	Telefax:+49(0)7720 948 337
<u>1.4. Emergency telephone</u> number:	+49 (0) 89-19240 (Giftnotruf Münd	chen, German and English 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling Dibenzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.

Precautionary statements

P261	Avoid breathing vapours.
P280	Wear protective gloves and eye/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to an approved waste disposal plant in accordance with



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 2 of 11

Sikla GmbH

local/national regulation.

2.3. Other hazards No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	Classification (GB CLP Regulation)			
94-36-0	Dibenzoyl peroxide		5 - < 15 %	
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE			
CAS No	EC No	Chemical name	Quantity
	Specific Conc	. Limits, M-factors and ATE	
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %
	oral: LD50 = Aquatic Chror	> 5000 mg/kg Aquatic Acute 1; H400: M=10 nic 1; H410: M=10	

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 3 of 11

5.1. Extinguishing media

Suitable extinguishing media

Foam Extinguishing powder Water spray jet Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat or drink.



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 4 of 11

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
94-36-0 Dibenzoyl peroxide				
Consumer DN	IEL, long-term	oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal		13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m³

PNEC values

CAS No	Substance		
Environmental compartment Va		Value	
94-36-0	Dibenzoyl peroxide		
Freshwater		0,00002 mg/l	
Marine water		0,000002 mg/l	
Freshwater sediment		0,013 mg/kg	
Marine sediment		0,001 mg/kg	

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 5 of 11



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves Recommended material: NBR (Nitrile rubber) Breakthrough time: > 480 min Thickness of the glove material: > 0,2 mm DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold:	solid (pasty) black characteristic No data available
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not determined not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	not applicable
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water: Vapour pressure:	not determined not determined



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Density (at 20 °C): Relative vapour density:

Self-ignition temperature

9.2. Other information

Solid:

Gas:

1,59 g/cm³ not determined

not determined not applicable

Not oxidising. Available oxygen content < 1% no classification Other safety characteristics

Information with regard to physical hazard classes

Evaporation rate: Solid content:

Oxidizing properties

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid Benzene Biphenyl

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
94-36-0	Dibenzoyl peroxide					
	oral	LD50 mg/kg	> 5000	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Page 6 of 11

not determined not determined

Sikla GmbH

VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 7 of 11

Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus) IC10: (0 - 72 h) = 30 mg/l IC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna) EC0/NOEC (48h) = 100 mg/l EC50 (48h) = >500 mg/l EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio) LC0/NOEC (96 h) : 250 mg/l LC50 (96 h) : > 500 mg/l LC100 (96 h) : >> 500 mg/l

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
94-36-0	Dibenzoyl peroxide							
	Acute fish toxicity	LC50 mg/l	0,0602		Oncorhynchus mykiss (Rainbow trout)	OECD 203		
	Acute algae toxicity	ErC50 mg/l	0,0711		Pseudokirchneriella subcapitata	OECD 201		
	Acute crustacea toxicity	EC50 mg/l	0,11		Daphnia magna (Big water flea)	OECD 202		
	Algae toxicity	NOEC mg/l	0,02		Pseudokirchneriella subcapitata	OECD 201		
	Crustacea toxicity	NOEC mg/l	0,001		Daphnia magna (Big water flea)	OECD 211		
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209		

12.2. Persistence and degradability

The product has not been tested.



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 8 of 11

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

Sikla GmbH

VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 9 of 11

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Inland waterways transport (ADN)

14.1. UN number or ID number:

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number:14.2. UN proper shipping name:14.3. Transport hazard class(es):14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u>

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 75 Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 10 of 11

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labeling and Packaging DMEL: Derived Minimal Effect level **DNEL: Derived No Effect Level** EC50: Effective concentration, 50% IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA) ICAO: International Civil Aviation Organization IC50: Inhibitory concentration, 50% IMDG: International Maritime Code for Dangerous Goods LC50: Lethal concentration. 50% LD50: Lethal dose, 50% NOEC: No Observed Effect Concentration OECD: Oragnisation for Economic Co-operation and Development PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail) VOC: Volatile organic compound Aquatic Acute 1: Acute aquatic hazard, Category 1 Aquatic Chronic 1: Long-term aquatic hazard, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Sens. 1: Skin sensitilization, Category 1 Org. Perox. B: Organic Peroxides, Type B

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



VMU plus, VMU plus 150, VMU plus 280, VMU plus 300, VMU plus 345, VMU plus 410 (Comp. B)

Revision date: 14.10.2022

Page 11 of 11

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)